urexam



Higher Quality

Better Service!

We offer free update service for one year Http://www.ourexam.com Exam : 500-254

Title : Implementing and

Configuring Cisco Identity

Service Engine - SISE

Version: Demo

- 1. Which two elements must you configure on a Cisco Wireless LAN Controller to allow Cisco ISE to authenticate wireless users? (Choose two.)
- A. Configure Cisco ISE as a RADIUS authentication server and enter a shared secret.
- B. Configure Cisco ISE as a RADIUS accounting server and enter a shared secret.
- C. Configure all attached LWAPs to use the configured Cisco ISE node.
- D. Configure RADIUS attributes for each SSID.
- E. Configure each WLAN to use the configured Cisco ISE node.
- F. Configure the Cisco Wireless LAN Controller to join a Microsoft Active Directory domain.

Answer: A,E

- 2. Which three Cisco TrustSec enforcement modes are used to help protect network operations when securing the network? (Choose three.)
- A. logging mode
- B. monitor mode
- C. semi-passive mode
- D. low-impact mode
- E. closed mode Answer: B.D.E
- 3. Which statement is correct about Change of Authorization?
- A. Change of Authorization is a fundamental component of Cisco TrustSec and Cisco ISE.
- B. Change of Authorization can be triggered dynamically based on a matched condition in a policy, and manually by being invoked by an administrator operation.
- C. It is possible to trigger Change of Authorization manually from the ISE interface.
- D. Authentication is the supported Change of Authorization action type.

Answer: D

- 4. The default Cisco ISE node configuration has which role or roles enabled by default?
- A. Administration only
- B. Inline Posture only
- C. Administration and Policy Service
- D. Policy Service, Monitoring, and Administration

Answer: D

- 5.Inline Posture nodes support which enforcement mechanisms?
- A. VLAN assignment
- B. downloadable ACLs
- C. security group access
- D. dynamic ACLs

Answer: B