

# Ourexam



---

**H i g h e r   Q u a l i t y**

**B e t t e r   S e r v i c e !**

We offer free update service for one year  
[Http://www.ourexam.com](http://www.ourexam.com)

**Exam** : **9L0-610**

**Title** : Xsan Administration v1.1  
Exam

**Version** : DEMO

**1.To view the WWPNs for an Apple Fibre Channel PCI-X card, use \_\_\_\_\_.**

- A.Xsan Admin
- B.Fibre Channel Utility
- C.RAID Utility
- D.cvadmin

**Correct:B**

**2.Which application allows you to monitor the status of disks within Xserve RAID LUNs?**

- A.Activity Monitor
- B.Disk Utility
- C.RAID Admin
- D.Xsan Admin

**Correct:C**

**3.Which statement is implied by the concept called "information lifecycle management"?**

- A.All information should be backed up in a weekly cycle.
- B.Disk-to-disk backup should be used for archival information.
- C.Information should be regularly cycled between backup devices.
- D.Storage resources should be allocated according to importance of data.

**Correct:D**

**4.Xsan is a \_\_\_\_\_ file system.**

- A.local
- B.cluster
- C.network
- D.distributed

**Correct:B**

**5.RAID Admin LUN mapping and masking features allow you to \_\_\_\_\_.**

- A.create folders that map data to a specified LUN or LUNs
- B.create LUNs that are available to only one client
- C.create LUNs that consist of a single dedicated drive
- D.add more disks to a LUN without taking the array offline

**Correct:B**

**6.Indicate the correct port settings when you configure an Emulex 355 switch for Xsan.**

- A.Host machine ports set as "Initiator with Stealth" and storage device ports set as "Target with Stealth."
- B.Host machine ports set as "Target with Stealth" and storage device ports set as "Initiator with Stealth."
- C.Both host machine ports and storage device ports set as "Initiator with Stealth."
- D.Both host machine ports and storage device ports set as "Target with Stealth."

**Correct:A**

**7.When naming an Xsan volume, which TWO statements are true? (Choose TWO.)**

- A.Any low-ASCII character can be used.
- B.Only letters and numbers can be used.
- C.Only lowercase letters and numbers can be used.
- D.Only uppercase letters and numbers can be used.
- E.Volume names can be up to 16 characters in length.
- F.Volume names can be up to 70 characters in length.
- G.Volume names can be up to 256 characters in length.

**Correct:B F**

**8.What is the recommended topology setting for the Apple Fibre Channel PCI-X card?**

- A.Automatic
- B.Point-to-point
- C.Arbitrated loop
- D.Switched fabric

**Correct:A**

**9.Fibre Channel Arbitrated Loop addresses use only the \_\_\_\_\_ field of Fabric Address Space.**

- A.Area
- B.Domain
- C.Loop
- D.Port

**Correct:D**

**10.Within a storage pool, Xsan stripes data over \_\_\_\_\_.**

- A.LUNs
- B.volumes
- C.disks
- D.affinities

**Correct:A**