

Ourexam



H i g h e r Q u a l i t y

B e t t e r S e r v i c e !

We offer free update service for one year
[Http://www.ourexam.com](http://www.ourexam.com)

Exam : JavaScript Developer I

**Title : Salesforce Certified
JavaScript Developer I**

Version : DEMO

1. At Universal Containers, every team has its own way of copying JavaScript objects. The code snippet shows an implementation from one team:

```
01 function Person() {
02   this.firstName = "John";
03   this.lastName = "Doe";
04   this.name = () => {
05     console.log(`Hello ${this.firstName} ${this.lastName}`);
06   }
07 }
08
09 const john = new Person();
10 const dan = JSON.stringify(JSON.parse(john));
11 dan.firstName = 'Dan';
12 dan.name();
```

What is the output of the code execution?

- A. Hello John Doe
- B. Hello Dan
- C. Hello Dan Doe
- D. SyntaxError: Unexpected token in JSON

Answer: D

2. CORRECT TEXT

Refer the following code

```
let array = [1, 2, 3, 4, 4, 5, 4, 4];
```

```
for(let i=0; i<array.length; i++)
```

```
{
```

```
  if(array[i]===4){
```

```
    array.splice(i, 1);
```

```
    i--;
```

```
  }
```

```
  alert(array);
```

what is the value of array after code executes?

Answer: [1, 2, 3, 5]

3.Refer to the code below:

```
let timeFunction =() => {  
console.log("Timer called.");  
};
```

```
let timerId = setTimeout (timeFunction, 1000);
```

Which statement allows a developer to cancel the scheduled timed function?

- A. `removeTimeout(timeFunction);`
- B. `removeTimeout(timerId);`
- C. `clearTimeout(timerId);`
- D. `clearTimeout(timeFunction);`

Answer: C

4.Which statement accurately describes the behaviour of the `async/ await` keywords?

- A. The associated class contains some asynchronous functions.
- B. The associated function will always return a promise
- C. The associated function can only be called via asynchronous methods
- D. The associated sometimes returns a promise.

Answer: B

5.A developer has two ways to write a function:

Option A:

```
function Monster() {  
This.growl = () => {  
Console.log ("Grr!");  
}  
}
```

Option B:

```
function Monster() {};  
Monster.prototype.growl =() => {  
console.log("Grr!");  
}
```

After deciding on an option, the developer creates 1000 monster objects.

How many growl methods are created with Option A Option B?

- A. 1 growl method is created for Option A. 1000 growl methods are created for Option B.
- B. 1000 growl method is created for Option A. 1 growl methods are created for Option B.
- C. 1000 growl methods are created regardless of which option is used.
- D. 1 growl method is created regardless of which option is used.

Answer: B